



MATERIALS
 HOUSING: HI-TEMP. PLASTIC (UL 94V-0)
 TERMINAL: COPPER ALLOY, GOLD PLATED ON CONTACT AREA
 TIN PLATING ON SOLDER TAIL

SPECIFICATION
 CURRENT RATING: 1.1 AMP MAX
 DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 30m OHMS MAX
 INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: -55°C~+105°C

CABLE 1

DIMENSIONS							
POS.	A	B	C	D	E	G	H
36	27.00	25.00	9.15	7.65	6.00	8.15	28.00
64	41.00	39.00	23.15	21.65	20.00	22.15	42.00
98	58.00	56.00	40.15	38.65	37.00	39.15	59.00
164	91.00	89.00	73.15	71.65	70.00	72.15	92.00

PART NUMBER: 4CEEE - * * * T - 1 * 0 * *

SERIES: 4CEEE
 NO. OF POS. REF. TABLE 1: * * *
 CONTACT PLATED OPTION: *
 1: GOLD FLASH
 3: 3u" GOLD
 5: 5u" GOLD
 6: 10u" GOLD
 9: 30u" GOLD

HOUSING COLOR OPTION: T
 BLANK: BLACK
 W: WHITE

POST OPTION: -
 BLANK: WITH POST
 1: W/O POST

PACKAGE OPTION: *
 1: TRAY
 2: TAPE REEL

TIN PLATING ON SOLDER TAIL: *

Cyberconn Technology Co., Ltd.
 www.cyberconn.com.tw Tel:+886-3-4951314

TOLERANCES	TITLE	CARD EDGE CONNECTOR SERIES				
X.X ±0.3 X.XX ±0.2 X.XXX ±0.1 Angle ±5°		PCI EXPRESS, 1.00mm PITCH, PCB MOUNT, SMT FEMALE, 1 KEY, WITH POST				
	DRAWN BY	CHECKED BY	APPROVED BY			
	Janice	Lion	Benson			
UNIT	SCALE	SIZE	DRAW NO.	REV.	Sheet	
10033	MM	NONE	A4	4CEEE-001	A 1/1	

A	RELEASE	2011.11.23
REV.	DESCRIPTION	DATE