



P.C.B LAYOUT TOP VIEW ±0.05

MATERIALS

HOUSING: LCP (UL 94V-0), BLACK
 SHELL: SUS, NICKEL PLATING
 TERMINAL: COPPER ALLOY, GOLD PLATED

SPECIFICATION

CURRENT RATING: 0.8 AMP MAX
 DIELECTRIC WITHSTANDING: 250V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 10m OHMS MAX
 INSULATION RESISTANCE: 100M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: -30°C~+85°C

PART NUMBER:

2HDLG - 1 9 * - 1 2 0

SERIES

NO. OF POS.

TAPE REEL PACKAGE

CONTACT PLATED OPTION

- 1: GOLD FLASH
- 3: 3u" GOLD
- 5: 5u" GOLD
- 7: 15u" GOLD
- 9: 30u" GOLD

Cyberconn Technology Co., Ltd. www.cyberconn.com.tw Tel:+886-3-4951314						
TOLERANCES		TITLE				
X.X ±0.3	X.XX ±0.2	HDMI CONNECTOR SERIES				
X.XXX ±0.1	Angle ±5'	MICRO HDMI, D TYPE, 0.40mm PITCH, PCB MOUNT, BOARD CUT TYPE, SMT, METAL SHIELD, FEMALE WITH EAR & MYLAR				
DRAWN BY		CHECKED BY		APPROVED BY		
Janice		Lion		Benson		
UNIT	SCALE	SIZE	DRAW NO.	REV.	Sheet	
10001	MM	NONE	A4	2HDLG-001	A 1/1	

A	RELEASE	2012.2.2
REV.	DESCRIPTION	DATE