



P.C.B. LAYOUT
TOP VIEW ±0.05

MATERIALS

HOUSING: LCP (UL 94V-0), BLACK
SHELL: STAINLESS STEEL, TIN PLATING
TERMINAL: COPPER ALLOY, GOLD PLATING

SPECIFICATION

CURRENT RATING: 1.8 AMP MAX (ONLY PIN 1, 5), OTHER 1 AMP MAX
DIELECTRIC WITHSTANDING: 100V AC FOR ONE MINUTE
CONTACT RESISTANCE: 30m OHMS MAX
INSULATION RESISTANCE: 100M OHMS MIN AT DC 500V
OPERATION TEMPERATURE: -25°C~+105°C

PART NUMBER:
2USTD - 0 5 * - 1 * 0

SERIES ————
NO. OF POS. ————
PACKAGE OPTION
2: TAPE REEL
3: TUBE

CONTACT PLATED OPTION
1: GOLD FLASH
3: 3u" GOLD
5: 5u" GOLD
7: 15u" GOLD
9: 30u" GOLD

B	MODIFY SOLDER PAD	2012.4.19
A	RELEASE	2012.4.18
REV.	DESCRIPTION	DATE

Cyberconn Technology Co., Ltd. www.cyberconn.com.tw Tel:+886-3-4951314						
TOLERANCES		USB CONNECTOR SERIES				
X.X ±0.3		TITLE MICRO USB B TYPE, PCB MOUNT, SMT, BOARD CUT TYPE				
X.XX ±0.2		METAL SHIELD, FEMALE				
X.XXX±0.1		DRAWN BY		CHECKED BY		APPROVED BY
Angle ±5°		Janice		Lion		Benson
		UNIT	SCALE	SIZE	DRAW NO.	REV.
10001		MM	NONE	A4	2USTD-001	B
						Sheet
						1/1