

HDMI TYPE A PIN ASSIGNMENT

PIN	Signal Assignment
1	TMDS Data2+
2	TMDS Data2 Shield
3	TMDS Data2-
4	TMDS Data1+
5	TMDS Data1 Shield
6	TMDS Data1-
7	TMDS Data0+
8	TMDS Data0 Shield
9	TMDS Data0-
10	TMDS Clock+
11	TMDS Clock Shield
12	TMDS Clock-
13	CEC
14	Reserved (N.C. on device)
15	SCL
16	SDA
17	DDC/CEC Ground
18	+5V Power
19	Hot Plug Detect

TABLE 1

ITEM	DIM A	DIM B
1	7.20	1.20
2	5.10	1.20
3	7.20	1.00
4	5.10	1.00

TABLE 2

ITEM	DIM. F	DIM. G
1	NON	0.90
2	0.15	0.90
3	0.30	1.10

PART NUMBER:
2HDBC - 1 9 * T - 1 2 2 * * *

SERIES ————
 NO. OF POS. ————
 CONTACT PLATED OPTION ————
 1: GOLD FLASH
 3: 3u" GOLD
 5: 5u" GOLD
 7: 15u" GOLD
 9: 30u" GOLD

MYLAR OPTION
 BLANK: WITHOUT MYLAR
 M: WITH MYLAR

"F & G" LENGTH OPTION
 REF TABLE 2


"A & B" LENGTH OPTION
 REF TABLE 1

TAPE REEL PACKAGE
 TIN PLATING ON SOLDER TAIL


MATERIALS
 HOUSING: HI-TEMP. PLASTIC (UL 94V-0)
 SHELL: COPPER ALLOY, NICKEL PLATING
 TERMINAL: COPPER ALLOY, GOLD PLATED ON CONTACT AREA
 TIN PLATING ON SOLDER TAIL

SPECIFICATION
 CURRENT RATING: 0.5 AMP MAX
 DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 30m OHMS MAX
 INSULATION RESISTANCE: 100M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: -20°C~+85°C

A	RELEASE	2012.8.22
REV.	DESCRIPTION	DATE



Cyberconn Technology Co., Ltd.
 www.cyberconn.com.tw Tel:+886-3-4951314

TOLERANCES		HDMI CONNECTOR SERIES					
X.X	±0.3	TITLE HDMI, PCB MOUNT, SMT, METAL SHIELD, FEMALE WITH EAR & SCREW					
X.XX	±0.2	DRAWN BY		CHECKED BY		APPROVED BY	
X.XXX	±0.1	<i>Janice</i>		<i>Lion</i>		<i>Benson</i>	
Angle	±5°	UNIT	SCALE	SIZE	DRAW NO.	REV.	Sheet
		10050	MM	NONE	A4	2HDBC-002	A 1/1