



MATERIALS

HOUSING: PBT (UL 94V-0)
 TERMINAL: COPPER ALLOY, GOLD PLATED
 WIRE: PVC 26AWG

SPECIFICATION

CURRENT RATING: 1.5 AMP MAX
 DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 30m OHMS MAX
 INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: -40°C~+85°C

TABLE 1

CONTACT POSITION	WIRE COLOR
1	BLACK
2	RED
3	GREEN
4	YELLOW
5	BROWN
6	WHITE

PART NUMBER:

3MJAA - 6 6 * - 1 4 1

SERIES

BAG PACKAGE

6 POSITION & 6 CONTACT

CONTACT PLATED OPTION

- 1: GOLD FLASH
- 3: 3u" GOLD
- 5: 5u" GOLD
- 7: 15u" GOLD
- 9: 30u" GOLD
- 11: 6u" GOLD

Cyberconn Technology Co., Ltd.
 www.cyberconn.com.tw Tel:+886-3-4951314

TOLERANCES	TITLE	MODULAR JACK SERIES				
X.X ±0.3	WIRE JACK, TOP ENTRY, 6P6C, ALL PLASTIC	DRAWN BY		CHECKED BY	APPROVED BY	
X.XX ±0.2		<i>Janice</i>		<i>Lion</i>	<i>Benson</i>	
X.XXX ±0.1		UNIT	SCALE	SIZE	DRAW NO.	REV.
Angle ±5°	10113	MM	NONE	A4	3MJAA-001	A
					Sheet	1/1

A	RELEASE	2012.9.17
REV.	DESCRIPTION	DATE