



MATERIALS

HOUSING: HI-TEMP. PLASTIC (UL 94V-0), BLACK
 SHELL: STAINLESS STEEL
 TERMINAL: COPPER ALLOY, GOLD PLATED ON CONTACT AREA
 TIN PLATING ON SOLDER TAIL

SPECIFICATION

CURRENT RATING: 0.5 AMP MAX
 DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 30m OHMS MAX
 INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: -25°C~+85°C

PART NUMBER:

4MCGF - 0 6 * T - 1 2 1

SERIES
 NO. OF POS.
 CONTACT PLATED OPTION
 TIN PLATING ON SOLDER TAIL
 TAPE REEL PACKAGE

Cyberconn Technology Co., Ltd.
 www.cyberconn.com.tw Tel: +886-3-4951314

TOLERANCES		MEMORY CARD SERIES				
X.X ±0.3		SIM CARD, 6 PIN, PCB MOUNT, SMT, METAL SHIELD FEMALE, HINGE TYPE				
X.XX ±0.2		DRAWN BY		CHECKED BY		APPROVED BY
X.XXX ±0.1		Janice		Lion		Benson
Angle ±5°		UNIT	SCALE	SIZE	DRAW NO.	REV.
		10099	MM	NONE	A4	4MCGF-001
						Sheet
						1/1

A	RELEASE	2012.9.21
REV.	DESCRIPTION	DATE