



P.C.B LAYOUT TOP VIEW ±0.05

PART NUMBER: 2SCCC - 3 6 8 * T - 1 1 0 *

SERIES: 2SCCC
PCB LAYOUT STYLE 3
NO. OF POS.: 3 6 8
CONTACT PLATED OPTION: 1: GOLD FLASH, 3: 3u" GOLD, 5: 5u" GOLD, 6: 10u" GOLD, 7: 15u" GOLD, 9: 30u" GOLD
TYPE OPTION: A: A TYPE, B: B TYPE
TRAY PACKAGE
TIN PLATING ON SOLDER TAIL

MATERIALS

HOUSING: PBT (UL 94V-0), BLACK
SHELL: STEEL, NICKEL PLATING
BOARD LOCK: COPPER ALLOY, TIN PLATING
TERMINAL: COPPER ALLOY, GOLD PLATED ON CONTACT AREA
TIN PLATING ON SOLDER TAIL

SPECIFICATION

CURRENT RATING: 0.5 AMP MAX
DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE
CONTACT RESISTANCE: 30m OHMS MAX
INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V
OPERATION TEMPERATURE: -55°C~+85°C

Cyberconn Technology Co., Ltd.
www.cyberconn.com.tw Tel:+886-3-4951314

TOLERANCES	TITLE	SCSI CONNECTOR SERIES				
X.X ±0.3 X.XX ±0.2 X.XXX±0.1 Angle ±5°		SCSI, 1.27mm PITCH, PCB MOUNT, R/A METAL SHIELD, FEMALE, 68PIN				
	DRAWN BY	CHECKED BY	APPROVED BY			
	Janice	Lion	Benson			
10021	UNIT	SCALE	SIZE	DRAW NO.	REV.	Sheet
	MM	NONE	A4	2SCCC-001	A	1/1

A	RELEASE	2012.5.31
REV.	DESCRIPTION	DATE