



PART NUMBER:
3MJFM - 4 4 * - 1 2 0

SERIES: 4 POSITION & 4 CONTACT
TAPE REEL PACKAGE: 1 CONTACT PLATED OPTION

- 1: GOLD FLASH
- 3: 3u" GOLD
- 5: 5u" GOLD
- 7: 15u" GOLD
- 9: 30u" GOLD
- 11: 6u" GOLD

MATERIALS

HOUSING: HI-TEMP. PLASTIC (UL 94V-0)
SOLDER PAD: COPPER ALLOY, TIN PLATING
TERMINAL: COPPER ALLOY, GOLD PLATED

SPECIFICATION

CURRENT RATING: 1.5 AMP MAX
DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE
CONTACT RESISTANCE: 30m OHMS MAX
INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V
OPERATION TEMPERATURE: -40°C~+85°C

Cyberconn Technology Co., Ltd.
www.cyberconn.com.tw Tel:+886-3-4951314

TOLERANCES	MODULAR JACK SERIES				
X.X ±0.3	TITLE				
X.XX ±0.2	RJ11, PCB MOUNT, TOP ENTRY, SMT TYPE				
X.XXX ±0.1	ALL PLASTIC				
Angle ±5°	DRAWN BY	CHECKED BY	APPROVED BY		
	Janice	Lion	Benson		
	UNIT	SCALE	SIZE	DRAW NO.	REV.
	10058	MM	NONE	A4	3MJFM-001
					Sheet
					1/1

A	RELEASE	2012.2.27
REV.	DESCRIPTION	DATE