



P.C.B LAYOUT
TOP VIEW ±0.05

MATERIALS

HOUSING: HI-TEMP. PLASTIC (UL 94V-0)
TERMINAL: COPPER ALLOY, GOLD PLATED

SPECIFICATION

DIELECTRIC WITHSTANDING: 200V AC FOR ONE MINUTE
CONTACT RESISTANCE: 20m OHMS MAX
INSULATION RESISTANCE: 500M OHMS MIN AT DC 100V
OPERATION TEMPERATURE: -40°C~+90°C

PART NUMBER:
5PXCA - 0 * * - 1 2 2

SERIES

TAPE REEL PACKAGE

GROUND CONTACT PLATED OPTION

- 1: GOLD FLASH
- 5: 5u" GOLD
- 9: 30u" GOLD
- S: SILVER

CENTER CONTACT PLATED OPTION

- 1: GOLD FLASH
- 5: 5u" GOLD
- 7: 15u" GOLD
- 9: 30u" GOLD

Cyberconn Technology Co., Ltd. www.cyberconn.com.tw Tel:+886-3-4951314						
TOLERANCES		TITLE I-PEX CONNECTOR SERIES				
X.X ±0.3		MICRO COAXIAL, SMT, FEMALE				
X.XX ±0.2		DRAWN BY		CHECKED BY		APPROVED BY
X.XXX ±0.1		Janice		Lion		Benson
Angle ±5°		UNIT		SCALE	SIZE	DRAW NO.
		MM	NONE	A4	5PXCA-002	REV. A
10115						Sheet 1/1

A	RELEASE	2011.10.5
REV.	DESCRIPTION	DATE