



MATERIALS

HOUSING: PA66 (UL 94V-0) YELLOW 114C
 BOTTOM HOUSING: PBT (UL 94V-0), YELLOW 114C
 TERMINAL: $\phi 0.46$ mm COPPER ALLOY, GOLD PLATED

SPECIFICATION

CURRENT RATING: 1.5 AMP MAX
 DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 30m OHMS MAX
 INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: $-40^{\circ}\text{C} \sim +85^{\circ}\text{C}$

PART NUMBER:

3MJBA - 8 8 * - 1 1 1

SERIES

TRAY PACKAGE

8 POSITION & 8 CONTACT

CONTACT PLATED OPTION

- 1: GOLD FLASH
- 3: 3u" GOLD
- 5: 5u" GOLD
- 7: 15u" GOLD
- 9: 30u" GOLD
- 11: 6u" GOLD

Cyberconn Technology Co., Ltd. <small>www.cyberconn.com.tw Tel:+886-3-4951314</small>						
TOLERANCES		TITLE				
X.X ±0.3		MODULAR JACK SERIES				
X.XX ±0.2		RJ45, PCB MOUNT, SIDE ENTRY, ALL PLASTIC				
X.XXX ±0.1		DRAWN BY		CHECKED BY		APPROVED BY
Angle ±5°		<i>Janice</i>		<i>Lion</i>		<i>Benson</i>
		UNIT	SCALE	SIZE	DRAW NO.	REV. Sheet
10003		MM	NONE	A4	3MJBA-001	A 1/1

A	RELEASE	2013.9.12
REV.	DESCRIPTION	DATE