



P.C.B. LAYOUT
TOP VIEW ±0.05

MATERIALS

HOUSING: HI-TEMP. PLASTIC (UL 94V-0), BLACK
 SHELL: STAINLESS STEEL, NICKEL PLATING
 TERMINAL: COPPER ALLOY, GOLD PLATED ON CONTACT AREA
 TIN PLATING NO SOLDER TAIL

SPECIFICATION

CURRENT RATING: 1.8 AMP MAX (ONLY PIN 1, 5), OTHER 1 AMP MAX
 DIELECTRIC WITHSTANDING: 100V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 30m OHMS MAX
 INSULATION RESISTANCE: 100M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: -25°C~+105°C

PART NUMBER:
2USTB - 0 5 * T - 1 * 0

SERIES ——— NO. OF POS. ——— PACKAGE OPTION
 2: TAPE REEL
 3: TUBE

CONTACT PLATED OPTION ——— TIN PLATING ON SOLDER TAIL

1: GOLD FLASH
 3: 3u" GOLD
 5: 5u" GOLD
 6: 10u" GOLD

Cyberconn Technology Co., Ltd. <small>www.cyberconn.com.tw Tel:+886-3-4951314</small>						
TOLERANCES		USB CONNECTOR SERIES				
X.X ±0.3		TITLE MICRO USB B TYPE, PCB MOUNT, SMT, METAL SHIELD, FEMALE, WITH POST				
X.XX ±0.2						
X.XXX ±0.1 Angle ±5°						
DRAWN BY		CHECKED BY		APPROVED BY		
<i>Janice</i>		<i>Lion</i>		<i>Benson</i>		
UNIT	SCALE	SIZE	DRAW NO.	REV.	Sheet	
10006&10057	MM	NONE	A4	2USTB-001	A 1/1	

A	RELEASE	2011.10.3
REV.	DESCRIPTION	DATE