



P.C.B. LAYOUT
TOP VIEW ±0.05

MATERIALS

HOUSING: HI-TEMP. PLASTIC (UL 94V-0), BLACK
 SHELL: COPPER ALLOY, NICKEL PLATING
 TERMINAL: COPPER ALLOY, GOLD PLATED ON CONTACT AREA
 TIN PLATING NO SOLDER TAIL

SPECIFICATION

CURRENT RATING: 1.8 AMP MAX (ONLY PIN 1, 5), OTHER 1 AMP MAX
 DIELECTRIC WITHSTANDING: 100V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 30m OHMS MAX
 INSULATION RESISTANCE: 100M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: -25°C~+105°C

PART NUMBER:
 2USTA - 0 5 * T - 1 * 7

SERIES — NO. OF POS. — PACKAGE OPTION
 2: TAPE REEL
 3: TUBE

CONTACT PLATED OPTION — TIN PLATING ON SOLDER TAIL

- 1: GOLD FLASH
- 3: 3u" GOLD
- 5: 5u" GOLD
- 6: 10u" GOLD
- 7: 15u" GOLD
- 9: 30u" GOLD

Cyberconn Technology Co., Ltd.
 www.cyberconn.com.tw Tel:+886-3-4951314

TOLERANCES		USB CONNECTOR SERIES				
X.X ±0.3	TITLE MICRO USB B TYPE, PCB MOUNT, SMT, METAL SHIELD FEMALE	DRAWN BY		CHECKED BY	APPROVED BY	
X.XX ±0.2		Janice		Lion	Benson	
X.XXX ±0.1		UNIT	SCALE	SIZE	DRAW NO.	REV.
Angle ±5°	10006&10057	MM	NONE	A4	2USTA-007	A
					Sheet	1/1

A	RELEASE	2013.7.22
REV.	DESCRIPTION	DATE