

MATERIALS

HOUSING: THERMOPLASTIC (UL 94V-0)
 SHELL: COPPER ALLOY, NICKEL PLATING
 TERMINAL: COPPER ALLOY, GOLD PLATED ON CONTACT AREA
 TIN PLATED ON SOLDER TAIL

SPECIFICATION


USB
 CURRENT RATING: 1 AMP MAX
 DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 50m OHMS MAX
 INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: -0°C~+70°C

RJ45
 CURRENT RATING: 1.5 AMP MAX
 DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 50m OHMS MAX
 INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: -0°C~+70°C

PART NUMBER:
71MJUS - 1 7 * T - 7 1 3

SERIES ————
 NO. OF POS. ————
 CONTACT PLATED OPTION ————
 TIN PLATING ON SOLDER TAIL ————
 TRAY PACKAGE

- 1: GOLD FLASH
- 3: 3u" GOLD
- 5: 5u" GOLD
- 7: 15u" GOLD
- 9: 30u" GOLD
- 11: 6u" GOLD



A	RELEASE	2013.11.13
REV.	DESCRIPTION	DATE

Cyberconn Technology Co., Ltd. www.cyberconn.com.tw Tel:+886-3-4951314						
TOLERANCES		COMBO CONNECTOR SERIES				
X.X ±0.3		TITLE STACKED RJ45 + USB 3.0, PCB MOUNT, SIDE ENTRY METAL SHIELD				
X.XX ±0.2		DRAWN BY		CHECKED BY		APPROVED BY
X.XXX ±0.1		<i>Janice</i>		<i>Lion</i>		<i>Benson</i>
Angle ±5°		UNIT		SCALE	SIZE	DRAW NO.
		10135		MM	NONE	A4
		REV.	Sheet			
		A	1/1			