



P.C.B LAYOUT  
TOP VIEW ±0.05

**MATERIALS**

HOUSING: THERMOPLASTIC (UL 94V-0)  
TERMINAL: Ø0.46mm COPPER ALLOY, GOLD PLATED

**SPECIFICATION**

CURRENT RATING: 1.5 AMP MAX  
DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE  
CONTACT RESISTANCE: 30m OHMS MAX  
INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V  
OPERATION TEMPERATURE: -40°C~+85°C

**PART NUMBER:**

3MJBA - 6 6 \* - 1 1 2

SERIES

TRAY PACKAGE

6 POSITION & 6 CONTACT

CONTACT PLATED OPTION

- 1: GOLD FLASH
- 3: 3u" GOLD
- 5: 5u" GOLD
- 7: 15u" GOLD
- 9: 30u" GOLD
- 11: 6u" GOLD

<b>Cyberconn Technology Co., Ltd.</b> <small>www.cyberconn.com.tw Tel:+886-3-4951314</small>						
TOLERANCES		MODULAR JACK SERIES				
X.X ±0.3		TITLE RJ12, PCB MOUNT, SIDE ENTRY, ALL PLASTIC				
X.XX ±0.2		DRAWN BY		CHECKED BY		APPROVED BY
X.XXX ±0.1		Tina		Lion		Benson
Angle ±5°		UNIT	SCALE	SIZE	DRAW NO.	REV. Sheet
		10145	MM	NONE	A4 3MJBA-002	A 1/1

A	RELEASE	2014.4.21
REV.	DESCRIPTION	DATE