



PART NUMBER:
4CEFT - 5 2 * - 1 2 5

SERIES NO. OF POS. TAPE REEL PACKAGE

- CONTACT PLATED OPTION
- 1: GOLD FLASH
 - 3: 3u" GOLD
 - 5: 5u" GOLD
 - 6: 10u" GOLD
 - 7: 15u" GOLD
 - 9: 30u" GOLD

MATERIALS

HOUSING: LCP (UL 94V-0)
SOLDER PAD: COPPER ALLOY, TIN PLATING
TERMINAL: COPPER ALLOY, GOLD PLATED

SPECIFICATION

CURRENT RATING: 0.5 AMP MAX
DIELECTRIC WITHSTANDING: 300V AC FOR ONE MINUTE
CONTACT RESISTANCE: 55m OHMS MAX
INSULATION RESISTANCE: 500M OHMS MIN AT DC 500V
OPERATION TEMPERATURE: -40°C~+85°C

INFORMATION

COMPATIBLE COPPER TUBE DRAWING NO:
94CEFT-001

COMPATIBLE SCREW DRAWING NO:
94CEFT-003

C	MODIFY HOLD DOWN SOLUTION	2014.2.17
B	ADD. PIN ASSIGNMENT	2014.1.7
A	RELEASE	2011.9.29
REV.	DESCRIPTION	DATE

Cyberconn Technology Co., Ltd.
www.cyberconn.com.tw Tel: +886-3-4951314

TOLERANCES		CARD EDGE CONNECTOR SERIES			
X.X ±0.3	TITLE	MINI PCI EXPRESS, 0.80mm PITCH, PCB MOUNT, SMT, FEMALE, 1 KEY, WITH PAD, HEIGHT=4.00mm			
X.XX ±0.2		DRAWN BY	CHECKED BY	APPROVED BY	
X.XXX ±0.1		<i>Janice</i>	<i>Lion</i>	<i>Benson</i>	
Angle ±5°		UNIT	SCALE	SIZE	DRAW NO.
	10022	MM	NONE	A4	4CEFT-003
				REV.	Sheet
				C	1/1