



PART NUMBER:
2USNQ - 1 0 * T - 2 2 1

SERIES ——— NO. OF POS. ——— TIN PLATING ON SOLDER TAIL ——— TAPE REEL PACKAGE

CONTACT PLATED OPTION ———

- 1: GOLD FLASH
- 3: 3u" GOLD
- 5: 5u" GOLD
- 6: 10u" GOLD
- 7: 15u" GOLD
- 9: 30u" GOLD

MATERIALS
 HOUSING: LCP (UL 94V-0)
 SHELL: SPCC, NICKEL PLATING
 TERMINAL: COPPER ALLOY, GOLD PLATED ON CONTACT AREA
 TIN PLATING ON SOLDER TAIL

SPECIFICATION
 DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 30m OHMS MAX
 INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V

Cyberconn Technology Co., Ltd. www.cyberconn.com.tw Tel:+886-3-4951314							
TOLERANCES		USB CONNECTOR SERIES					
X.X ±0.3		TITLE MINI USB, PCB MOUNT, VERTICAL, METAL SHIELD MALE, 10PIN, SOLDER MOUNT					
X.XX ±0.2							
X.XXX ±0.1		DRAWN BY		CHECKED BY		APPROVED BY	
Angle ±5°		<i>Tina</i>		<i>Lion</i>		<i>Benson</i>	
		UNIT	SCALE	SIZE	DRAW NO.	REV.	Sheet
		10006&10057	MM	NONE	A4	2USNQ-001	A

A	RELEASE	2014.7.7
REV.	DESCRIPTION	DATE