

P.C.B. LAYOUT
TOP VIEW ±0.05


MATERIALS

HOUSING: HI-TEMP. PLASTIC (UL 94V-0)
 SHELL: COPPER ALLOY OR SUS, NICKEL PLATING
 TERMINAL: COPPER ALLOY, GOLD PLATED ON CONTACT AREA
 TIN PLATING ON SOLDER TAIL

SPECIFICATION

CURRENT RATING: 1 AMP MAX
 DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 30m OHMS MAX
 INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: -25°C~+85°C

PART NUMBER:



A	RELEASE	2014.10.13
REV.	DESCRIPTION	DATE

<p>Cyberconn Technology Co., Ltd. www.cyberconn.com.tw Tel: +886-3-4951314</p>						
TOLERANCES		USB CONNECTOR SERIES				
X.X ±0.3		TITLE USB A TYPE, PCB MOUNT, SMT, METAL SHIELD FEMALE				
X.XX ±0.2		DRAWN BY		CHECKED BY		APPROVED BY
X.XXX ±0.1		Tina		Lion		Benson
Angle ±5°		UNIT	SCALE	SIZE	DRAW NO.	REV. Sheet
		10134	MM	NONE	A4	2USAB-009 A 1/1