



P.C.B. LAYOUT
TOP VIEW ±0.05

MATERIALS

HOUSING: THERMOPLASTIC (UL 94V-0)
SHELL: COPPER ALLOY, NICKEL PLATING
TERMINAL: φ0.46mm COPPER ALLOY, GOLD PLATED

SPECIFICATION

CURRENT RATING: 1.5 AMP MAX
DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE
CONTACT RESISTANCE: 30m OHMS MAX
INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V
OPERATION TEMPERATURE: -40°C~+85°C

PART NUMBER:

3MJBC - 8 8 * 2 - 1 1 3

- SERIES
- 8 POSITION & 8 CONTACT
- REAR PCB STOP
- CONTACT PLATED OPTION
 - 1: GOLD FLASH
 - 3: 3u" GOLD
 - 5: 5u" GOLD
 - 7: 15u" GOLD
 - 9: 30u" GOLD
 - 11: 6u" GOLD
- TRAY PACKAGE

| | | |
|------|-------------|-----------|
| A | RELEASE | 2013.3.11 |
| REV. | DESCRIPTION | DATE |

Cyberconn Technology Co., Ltd.
www.cyberconn.com.tw Tel:+886-3-4951314

| | | | | | | |
|------------|--|--|-------|-------------|----------|---------------|
| TOLERANCES | | MODULAR JACK SERIES | | | | |
| X.X ±0.3 | | TITLE | | | | |
| X.XX ±0.2 | | RJ45, PCB MOUNT, SIDE ENTRY, METAL SHIELD, REAR PCB STOP | | | | |
| X.XXX ±0.1 | | DRAWN BY | | CHECKED BY | | APPROVED BY |
| Angle ±5° | | <i>Janice</i> | | <i>Lion</i> | | <i>Benson</i> |
| | | UNIT | SCALE | SIZE | DRAW NO. | REV. |
| | | 10003 | MM | NONE | A4 | 3MJBC-003 |
| | | | | | Sheet | |
| | | | | | 1/1 | |