


Pin No.	MICRO SD
PIN1	DAT2 1P
PIN2	CD/DAT3 2P
PIN3	CMD 3P
PIN4	VDD 4P
PIN5	CLK 5P
PIN6	VSS 6P
PIN7	DAT0 7P
PIN8	DAT1 8P



PCB LAYOUT
 THIS AREA CAN NOT BE PRINTED CIRCUIT (PART MOUNTING SIDE)
 PRODUCT APPEARANCE
P.C.B LAYOUT TOP VIEW ±0.05

PART NUMBER:
4MCKB - 0 8 * - 1 2 3

SERIES — NO. OF POS. — TAPE REEL PACKAGE

- TERMINAL PLATED OPTION
- 1: GOLD FLASH
 - 3: 3u" GOLD
 - 5: 5u" GOLD
 - 6: 10u" GOLD
 - 7: 15u" GOLD
 - 9: 30u" GOLD

SPECIFICATION

CURRENT RATING: 0.5 AMP MAX
 DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 100m OHMS MAX
 INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: -25°C~+65°C

MATERIALS

HOUSING: HI-TEMP. PLASTIC (UL 94V-0), BLACK
 SHELL: STAINLESS STEEL, NICKEL PLATING
 TERMINAL: COPPER ALLOY, GOLD PLATED
 SOLDER PAD: STAINLESS STEEL, GOLD PLATING

A	RELEASE	2014.7.16
REV.	DESCRIPTION	DATE

Cyberconn Technology Co., Ltd.
 www.cyberconn.com.tw Tel:+886-3-4951314

TOLERANCES	MEMORY CARD SERIES					
X.X ±0.3	MICRO SD, PCB MOUNT, SMT, METAL SHIELD					
X.XX ±0.2	PUSH-PULL TYPE, FEMALE, H=1.28mm					
X.XXX ±0.1	DRAWN BY		CHECKED BY		APPROVED BY	
Angle ±5°	Tina		Lion		Benson	
	UNIT	SCALE	SIZE	DRAW NO.	REV.	Sheet
	10154	MM	NONE	A4	4MCKB-003 A	1/1