


P.C.B. LAYOUT
TOP VIEW ±0.05



MATERIALS

HOUSING: PBT (UL 94V-0)
 INNER PIN: COPPER ALLOY, SILVER PLATING
 TERMINAL: COPPER ALLOY, SILVER PLATING

SPECIFICATION

DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 50m OHMS MAX
 INSULATION RESISTANCE: 100M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: -25°C ~+85°C

PART NUMBER:

3PJAB - 9 - 1 4 6

SERIES

BAG PACKAGE

∅0.65mm INNER PIN

Cyberconn Technology Co., Ltd. <small>www.cyberconn.com.tw Tel:+886-3-4951314</small>						
TOLERANCES	DC POWER JACK CONNECTOR SERIES					
X.X ±0.3	TITLE					
X.XX ±0.2	DC POWER JACK, PCB MOUNT, R/A, FEMALEM, WITH POST					
X.XXX ±0.1	DRAWN BY	CHECKED BY	APPROVED BY			
Angle ±5°	<i>Tina</i>	<i>Lion</i>	<i>Benson</i>			
	UNIT	SCALE	SIZE	DRAW NO.	REV.	Sheet
	10053	MM	NONE	A4	3PJAB-006	A 1/1

A	RELEASE	2015.3.12
REV.	DESCRIPTION	DATE