

P.C.B LAYOUT
TOP VIEW ±0.05

MATERIALS

HOUSING: PBT (UL 94V-0), BLACK
 INNER PIN: COPPER ALLOY, NICKEL PLATING
 TERMINAL: COPPER ALLOY, TIN PLATING

SPECIFICATION

DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 30m OHMS MAX
 INSULATION RESISTANCE: 100M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: -25°C~+85°C

PART NUMBER:


3PJAA - * - 1 4 1

SERIES

BAG PACKAGE

INNER PIN OPTION

2: Ø2.50mm
 4: Ø2.00mm



A	RELEASE	2012.8.15
REV.	DESCRIPTION	DATE

Cyberconn Technology Co., Ltd.
 www.cyberconn.com.tw Tel:+886-3-4951314

TOLERANCES	TITLE	DC POWER JACK CONNECTOR SERIES				
X.X ±0.3 X.XX ±0.2 X.XXX ±0.1 Angle ±5°		DC POWER JACK, PCB MOUNT, R/A, FEMALE				
	DRAWN BY	CHECKED BY	APPROVED BY			
	Janice	Lion	Benson			
10053	UNIT	SCALE	SIZE	DRAW NO.	REV.	Sheet
	MM	NONE	A4	3PJAA-001	A	1/1