




**MATERIALS**


HOUSING: HI-TEMP. PLASTIC (UL 94V-0)  
 SHELL: IRON, NICKEL PLATING  
 TERMINAL: COPPER ALLOY, GOLD PLATED ON CONTACT AREA  
 TIN PLATING ON SOLDER TAIL

**SPECIFICATION**

CURRENT RATING: 1 AMP MAX  
 DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE  
 CONTACT RESISTANCE: 30m OHMS MAX  
 INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V  
 OPERATION TEMPERATURE: -25°C~+85°C



P.C.B. LAYOUT  
 TOP VIEW ±0.05



PART NUMBER:  
**2USAL - 0 4 \* T - 1 1 5 \***

SERIES — NO. OF POS. — CONTACT PLATED OPTION — TRAY PACKAGE — HOUSING COLOR OPTION  
 BLANK: BLACK  
 W: WHITE

TIN PLATING ON SOLDER TAIL

1: GOLD FLASH  
 3: 3u" GOLD  
 5: 5u" GOLD  
 6: 10u" GOLD  
 7: 15u" GOLD  
 9: 30u" GOLD

**Cyberconn Technology Co., Ltd.**  
 www.cyberconn.com.tw Tel:+886-3-4951314

TOLERANCES	USB CONNECTOR SERIES				
X.X ±0.3	TITLE USB A TYPE, PCB MID MOUNT, REVERSE TYPE				
X.XX ±0.2	R/A, METAL SHIELD, FEMALE				
X.XXX ±0.1	DRAWN BY	CHECKED BY	APPROVED BY		
Angle ±5°	<i>Placy</i>	<i>Lion</i>	<i>Benson</i>		
UNIT	SCALE	SIZE	DRAW NO.	REV.	Sheet
	MM	NONE	A4	2USAL-005	A 1/1

A	RELEASE	2012.10.4
REV.	DESCRIPTION	DATE