



MATERIALS

HOUSING: THERMOPLASTIC (UL 94V-0)
 SHELL: SPCC, NICKEL PLATING
 TERMINAL: COPPER ALLOY, GOLD PLATED ON CONTACT AREA
 TIN PLATING ON SOLDER TAIL

SPECIFICATION

CURRENT RATING: 1 AMP MAX
 DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 30m OHMS MAX
 INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: -40°C~+85°C

PART NUMBER:

2USAE - 0 4 * T - 2 * A *

SERIES — NO. OF POS. — CONTACT PLATED OPTION — TIN PLATING ON SOLDER TAIL — HOUSING COLOR OPTION — PACKAGE OPTION

BLANK: BLACK
 W: WHITE

1: GOLD FLASH
 3: 3u" GOLD
 5: 5u" GOLD
 6: 10u" GOLD
 7: 15u" GOLD
 9: 30u" GOLD

1: TRAY
 2: TAPE REEL

Cyberconn Technology Co., Ltd.
 www.cyberconn.com.tw Tel:+886-3-4951314

TOLERANCES		TITLE				
X.X	±0.3	USB CONNECTOR SERIES				
X.XX	±0.2	USB A TYPE, PCB MID MOUNT, R/A				
X.XXX	±0.1	METAL SHIELD, MALE				
Angle	±5°	DRAWN BY		CHECKED BY		APPROVED BY
		<i>Tina</i>		<i>Lion</i>		<i>Benson</i>
UNIT	SCALE	SIZE	DRAW NO.	REV.	Sheet	
	10196	MM	NONE	A4	2USAE-010	A 1/1

A	RELEASE	2016.3.2
REV.	DESCRIPTION	DATE